
HORIZONTAL MAGNETIC LEVEL SWITCH EXPLOSION PROOF LXT201 Thread Type


Technical Data

Enclosure housing: Explosion proof- EEx d II C T6, IP65
Process connection: 1½"~3"NPT male, thread type
Material: Wetted parts 316 stainless steel
Pressure limits: 3.0 MPa (30 kg/cm²), option: up to 4.5 MPa
Float working specific gravity: ≥0.7
(option: less than 0.7 available on request)
Maximum temperature: -20°C to +150°C
Switch function: Micro switch 1 x SPDT; 2 x SPDT option
Switch rating: 3A/250VAC, 3A/30VDC, 0.4A/125VDC
Conduit connection: ½"NPT, ¾"NPT female, option available




Dimensions

Standard Tpye



Extension Arm Type



*Option: Extension arm specify length available (standard 150mm).

unit=mm

Ordering Information

LXT201	Code	Type		
	S	Standard type	E	Extension Arm Type

Code	Process Connection Size
	(1) 1½" (2) 2" (3) 3" (4) Option


Code	Process Connection Rating - Male
	(A) NPT (B) Option

Code	Conduit Connection Size
	(1) ½"NPT (2) ¾"NPT (3) Option

Code	Wetted Parts Material
	(1) SS316 (2) Option

Code	Switch Function- Micro Switch
1	One switch, SPDT x 1
2	Two switch, SPDT x 2

LXT201							Complete Ordering Code



Wire Drawing

WWW.NEW-FLOW.DE | Tel: +49 3682 49099 | Fax: +49 3682 49093 | E-Mail: info@mess-regel.de