PRESSURE SWITCH NEMA 4, 4X, IP65

PS2100W

Proof Pressure to 1000psi
Adjustable Ranges: 2~100psi
Temperature: -20 to 205°C




The New-Flow PS2100W, a water proof pressure switch, is designed to be used in control systems. PS2100W has high set point repeatability and narrow dead band features. A variety of range selections are available upon request. Easily adjusted to the set point, and no special tools needed!

Technical Data

Switch Data: one SPDT & two SPDT Microswitch, 15amps 125/250VAC, Gold Contact Microswitch 1A 125/250VAC
Housing: die cast aluminum alloy with paint
Conduit Connection: ¾" or ½" NPT Female
Pressure Element: welded type diaphragm
Process Materials: wetted parts are all in SS316
Process Connection: ½" or ¼" NPT Female

Dimensions



Range Selection Table

Code	Adjustable Range	Dead Band	Maximum Pressure Proof
04R	2~12psi	0.2~0.4	1000psi
10R	2~16psi	0.2~0.5	1000psi
20R	2~20psi	0.3~0.6	1000psi
30R	3~28psi	0.3~0.8	1000psi
40R	7~100psi	0.7~2.0	1000psi

Ordering Information

PS2100W	Code	Range									
		04R	2~12psi	**10R**	2~16psi	**20R**	2~20psi	**30R**	3~28psi	**40R**	7~100psi

Code	Wetted Material
A	SS316

Code	Process Connection
	(1) ½" NPT Female **(2)** ¼" NPT Female

Code	Conduit Connection
	(E) ¾" NPT Female **(F)** ½" NPT Female, standard

Code	Switch Form
1	One SPDT
2	Two SPDT (one setting point)
3	Gold Contact (SPDT)

PS2100W						Complete Ordering Code

WWW.NEW-FLOW.DE | Tel: +49 3682 49099 | Fax: +49 3682 49093 | E-Mail: info@mess-regel.de